



a duct tape catalog

## GMDT-14

Economy Grade  
Duct Tape



### Product Description

An economic grade Duct Tape coated with Hotmelt adhesive for strong hold. It is water resistant and easy to tear.

### Features

Good holding power, tensile strength and able to conform to various surface, water proof and easy tear

### Main Applications

General bundling, sealing, color coding, marking & repairing jobs

### Technical Data

	Metric	Imperial Units	Test Method
Total weight*	110 g/m2	110 g/m2	ISO 536
Total thickness*	140 µm	5.5 mils	AFERA 5006/PSTC 133
MD tensile strength*	34 N/cm	19.4 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	20 %	20 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	6 N/cm	54.8 oz/in	AFERA 5001/PSTC 101

#### Backing material

PE laminated synthetic cloth

#### Type of adhesive

Synthetic rubber resin – solvent free

\*Typical value

#### Available colors

    
Silver Black White

## GMDT-16

Utility Grade  
Duct Tape



### Product Description

An economic grade Duct Tape coated with Hotmelt adhesive. Commonly used for sealing and protection from damages.

### Features

Good holding power, tensile strength and able to conform to various surface, water proof and easy tear

### Main Applications

General bundling, sealing, color coding, marking & repairing jobs

### Technical Data

	Metric	Imperial Units	Test Method
Total weight*	154 g/m2	154 g/m2	ISO 536
Total thickness*	165 µm	6.5 mils	AFERA 5006/PSTC 133
MD tensile strength*	37 N/cm	21.1 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	20 %	20 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	9.5 N/cm	86.8 oz/in	AFERA 5001/PSTC 101

#### Backing material

PE laminated synthetic cloth

#### Type of adhesive

Synthetic rubber resin – solvent free

\*Typical value

#### Available colors

          
Silver Black White Red Orange Yellow Green Blue Olive green

# GMDT-17

Professional Grade Duct Tape



## Product Description

A professional grade Duct Tape coated with Hotmelt adhesive for strong holding power and adhesion

## Features

Strong holding power, good conformability, low temp resistance, waterproof and easy-tear.

## Main Applications

General repair, masking, pipe wrapping, duct seaming and unit sealing

## Technical Data

	Metric	Imperial Units	Test Method
Total weight*	153 g/m2	153 g/m2	ISO 536
Total thickness*	165 µm	6.5 mils	AFERA 5006/PSTC 133
MD tensile strength*	33 N/cm	18.8 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	20 %	20 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	9 N/cm	82.2 oz/in	AFERA 5001/PSTC 101
Service temperature	-10°C / 60°C	14°F / 140°F	

**Backing material**  
PE laminated synthetic cloth

**Type of adhesive**  
Synthetic rubber resin – solvent free

\*Typical value

### Available colors

      
Silver Black White Yellow Blue

# GMDT-21

Medium Grade Duct Tape



## Product Description

A professional grade Duct Tape coated with Hotmelt adhesive for excellent holding power and challenging construction jobs.

## Features

Strong holding power, good conformability, low temp resistance, waterproof and easy-tear.

## Main Applications

General repair, masking, pipe wrapping, duct seaming and unit sealing

## Technical Data

	Metric	Imperial Units	Test Method
Total weight*	180 g/m2	180 g/m2	ISO 536
Total thickness*	210 µm	8.3 mils	AFERA 5006/PSTC 133
MD tensile strength*	40 N/cm	22.8 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	17 %	17 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	9 N/cm	82.2 oz/in	AFERA 5001/PSTC 101
Service temperature	-10°C / 60°C	14°F / 140°F	

**Backing material**  
PE laminated synthetic cloth

**Type of adhesive**  
Synthetic rubber resin – solvent free

\*Typical value

### Available colors

       
Silver Black White OrangeYellow Blue

# GMDT-23

## Premium Duct Tape



### Product Description

Premium quality duct tape coated with Hotmelt adhesive is suitable for construction application and other heavy duty use.

### Features

Strong holding power with abrasion and weather resistance. Able to conform to various surface & easy tear.

### Main Applications

Pipe wrap and duct seaming and general bundling application.

### Technical Data

	Metric	Imperial Units	Test Method
Total weight*	200 g/m2	200 g/m2	ISO 536
Total thickness*	225 µm	8.9 mils	AFERA 5006/PSTC 133
MD tensile strength*	42 N/cm	24 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	16 %	16 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	10 N/cm	91.4 oz/in	AFERA 5001/PSTC 101
Service temperature	-10°C / 60°C	14°F / 140°F	

**Backing material**  
PE laminated synthetic cloth

**Type of adhesive**  
Synthetic rubber resin - solvent free

\*Typical value

### Available colors



Silver Black



**DUCT TAPE THAT  
STICKS AND STAYS**

- LEAVES NO RESIDUE BEHIND
- EFFORTLESS APPLICATION AND REMOVAL



**Great stretch and  
conformability**



Perfect for both indoor  
and outdoor applications



**Multi-Purpose**  
Fix, stick things together  
or seal any hole or box.



**GTG MANUFACTURING SDN. BHD. (968289-M)**

Website: [www.gtggroup.com.my](http://www.gtggroup.com.my)

Tel: +603-8725 9988 | Fax: +603-8725 9989 | Email: [info@gtggroup.com.my](mailto:info@gtggroup.com.my)

