

# **CLOTH/DUCT TAPE** - NATURAL RUBBER



#### **Product Features**

Woven Polyester & Cotton Blended with LDPE & Coated with Natural Rubber

## Application


For non-critical, general use in packaging, bundling, sealing, repairing, holding, book binding, carpet joining, taping / splicing insulation, reinforcing, patching, tabbing, marking & labelling



















## Technical Data

Product	Adhesive	Total Thickness		Initial Tack	Peel Adhesion		Tensile Strength		Elongation % at break
		(um)	(mil)	(#)	(N/in)	ASTM D-3330 (oz/in)	(N/in)	ASTM D-3759 (lb/in)	ASTM D-3759
CTNB23	Natural Rubber	230	9.1	15†	8 <b>†</b>	29	70 <b>†</b>	16	15%
CTNB25	Natural Rubber	250	9.8	18 <del>1</del>	8 <b>†</b>	29	95†	21	15%
CTNB27	Natural Rubber	270	10.6	20†	8†	29	95†	21	15%
CTNB30	Natural Rubber	300	11.8	23†	9t	32	95†	21	15%
CTNB36	Natural Rubber	360	14.2	25†	9t	32	95†	21	15%
CTNB42	Natural Rubber	420	17.5	25†	10 <b>†</b>	36	95†	18	15%

## **Product Sizes**

Jumbo Roll Size Paper Core Size Cut Size :1060mm x 500m :76mm

:48mm x 5m (\*Custom sizes available)

## **Product Characteristics**

- Good conformability
- Designed for heavy duty
- Removes cleanly for up to three months when applied indoors
- Sticks immediately and stays on for up to one year without deterioration
- Strong water-resistant backing resists wear and light abrasion
- Provides a tight, moisture-resistant seal in many containment situations

## Shelf Life

12 Months Storage at 23°C and 65% Relative Humidity

