




# CLOTH/DUCT TAPE - SYNTHETIC RUBBER

## Product Features

Woven Polyester & Cotton Blended with LDPE & Coated with Synthetic Rubber Adhesive

## Application

For non-critical, general use in patching bundling, reinforcing taping / splicing insulation, capping pipe, protecting against light sandblast overspray, packaging, sealing, repairing, carpet joining, marking & labelling



## Product Sizes

Jumbo Roll Size : 1060mm x 500m  
Paper Core Size : 76mm  
Cut Size : 48mm x 5m  
(\*Custom sizes available)

## Technical Data

Product	Adhesive	Total Thickness		Initial Tack	Peel Adhesion		Tensile Strength		Elongation % at break
		(um)	(mil)	(#)	(N/in)	ASTM D-3330 (oz/in)	(N/in)	ASTM D-3759 (lb/in)	ASTM D-3759
CTSR423	Synthetic Rubber	230	9.1	12†	19†	68	95†	21	15%
CTSR425	Synthetic Rubber	250	9.8	13†	19†	68	95†	21	15%
CTSR427	Synthetic Rubber	270	11.0	14†	23†	83	95†	21	15%

## Product Characteristics

- Water-resistant backing seals and protects against humidity and moisture
- Tears cleanly across and down for easy handling and application
- Aggressive, synthetic rubber adhesive provides instant adhesion to a wide variety of surfaces, including metal, glass, plastic and sealed concrete
- Tears easily by hand and provides ease of application and handling
- Conformable backing allows for performance in a variety of surface applications
- Tightly woven scrim provides high tensile strength, which is ideal for bundling applications

## Shelf Life

12 Months Storage at 23 °C and 65% Relative Humidity

*Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.*