



# CELLULOSE TAPE



## Product Features

Cellulose Film Coated with Rubber Based Adhesive

## Application

Suitable for attaching, mending, sealing, bundling, protecting, repairing, gift wrapping, card making, memo attachment and securing light weight items



## Technical Data

Product	Total Thickness	Tensile Strength	Adhesion to Steel	Temperature Resistance	Elongation % at break
	(mm)	ASTM D-3759 (lb/in)	(oz/in)	(°C)	ASTM D-3759
CT05	0.5	25	40	80	20

\*The above data comes with a min tolerance of  $\pm 5\%$

## Product Characteristics

- Highly conformable on most surfaces
- Low temperature resistance
- The tape has a yellow brownish-hue on the roll, but is clear when applied
- Hand tearable, can be torn by hand easily without using scissors
- Eco-friendly since it is biodegradable
- Easy to manipulate and excellent operation with packaging machines
- Excellent adhesion with good holding power as well as exceptional shear properties due to strong intermolecular force which provide good attachment effect
- Antistatic, good elimination of electrostatic due to uniform hydrophilic and hydrophobic properties, often used in the electronics industry since it is static-free

## Product Sizes

Jumbo Roll Sizes :1280mm x 4000m  
Cut Sizes :As per customer requirements

## Shelf Life

12 Months Storage at 23°C and 65% Relative Humidity



Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.