

FILAMENT TAPE - CROSSED LINE



Product Features

BOPP Film with Reinforced Glass Yarn Filament Coated with Synthetic Rubber Adhesive

Application

Great for heavy-duty splicing, packing, bundling, reinforcing and palletizing. Ideal for heavy-weight packages overseas/ export packing and shipping

White

Tec	h	nic	al	Da	ta

Product V	Woven		tal kness	Initial Tack	Peel Adhesion		Tensile Strength		Elongation % at break
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	(um)	(mil)	(#)	(N/in)	ASTM D-3330 (oz/in)	(N/in)	ASTM D-3759 (lb/in)	ASTM D-3759
FTCW12	Cross Weave	120	4.7	8	6	22	600	134	12%
FTCW14	Cross Weave	140	5.5	10	18	65	800	180	12%
FTCW17	Cross Weave	170	6.7	12	20	72	1000	220	12%

Product Characteristics

- Glass yarn filaments add strength for box closing and bundling
- Excellent long term holding power
- High shear, high tack adhesive for strong holding power
- Hold instantly with minimum rubdown
- Nicks, abrasion, scuffing resistant
- Moisture resistance, superior resistance against mildew and mold
- Weatherproof, UV and temperature resistant
- Bi-directionally fibreglass reinforced tape provides cut and tear resistance in machine direction and cross direction
- Able to withstand roughest shipping and handling conditions

Product Sizes

Jumbo Roll Size :1060mm x 1000m

Paper Core Size :76mm

Cut Size :As per customer requirements

Shelf Life

12 Months Storage at 23°C and 65% Relative Humidity

Disclaimer: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.