




ANTI-SLIP TAPE

Product Features

A Thick PVC Base Layer Infused with Quartz Sand and Coated with Water Based Acrylic & Acrylic Solvent Adhesive

Application

Boosts traction and reduces the risk of slips and falls. Suitable for walkways, stair edgings and ramps for greater safety and stability. Designed to bond to rough or smooth surfaces



Technical Data

Product	Thickness Of Backing	Total Thickness		Temperature Resistance		Tensile Strength	Holding Power
	(um)	(um)	(mil)	(°C)	(°F)	(N/in)	12 hours
AST320	100	700	27.6	105	221	13	5N

Product Characteristics

- Provides a durable and reliable non-slip surface to create a safer environment
- Leaves no residues after peeling off
- Easy to cut to fit to meet all needs of stair or floor dimensions
- Fixes wet, smooth, greasy and oily floors
- Water, chemical and oil resistant for use in both indoor & outdoor applications
- Withstands heavy foot traffic under all weather conditions
- Withstands temperatures up to 221 F
- Form a strong, water-proof bond to most any clean, dry surface and is also temporarily repositionable during the application process

Product Sizes

Paper Core Size : 76mm
Cut Size : 50mm/25mm x 5m (*Custom sizes available)

Shelf Life

12 Months Storage at 23°C and 65% Relative Humidity



Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.