

DOUBLE SIDED ACRYLIC FOAM TAPE



Product Features

Double Sided Acrylic Foam Coated with Silicone Rubber Adhesive

Application

Typically used for mounting of sign and display, mounting of badge and fixing of vehicle panel. Widely applied on metal, glass, plastic, composite, sealed wood, paint, attachment of automotive exterior parts, and powder coating

Technical Data

Product	Backing	Adhesive	Total Thickness		Peel Adhesion	
			(um)	(mil)	(N/in)	ASTM D-3330 (oz/in)
DSAFT5	VHB white	Acrylate	1	2.4	12↑	43
DSAFT2	VHB white	Acrylate	50	2.8	13↑	47
DSAFT3	VHB white	Acrylate	80	3.2	15↑	54
DSAFT4	VHB white	Acrylate	150	3.5	15↑	54
DSAFT1	VHB white	Acrylate	200	3.9	17↑	61
DSAFT6	VHB grey	Acrylate	800	3.5	10↑	54





(Acrylic Foam) with recolor PE Release Liner



Holding Toothbrush Hanging Stand

Mounting Dashboard Decoration/ Handphone Holder



Holding Wall Picture Frame

Sticking Number Plate



Product Characteristics

- Highly conformable and able to stick on irregular and mismatched substrates
- Excellent flexibility and good tensile strength
- Acrylic foam with good flexibility reduce peeling stress
- Excellent capability in shock absorption and play an excellent role in vibration weakening
- Long-term durability and good thermal resistance
- Provides cushioning
- Virtually invisible fastening keeps surfaces smooth
- Bonds well to metals, glass, painted surfaces, and medium/low surface energy plastics
- Superior bonding strength, good anti-aging properties and unaffected by ultra-violet light (UV)
- Excellent high temperature resistant, good adhesion, climate resistant, oil resistant and waterproof
- Replace mechanical fasteners (rivets, welds, screws) or liquid adhesives, eliminate drilling, grinding, refinishing, screwing, welding and associated clean-up

Product Sizes

Log Roll Size : 800mm x 8m
Cut Size : As per customer requirements

Shelf Life

12 Months Storage at 23°C and 65% Relative Humidity

Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.