



MEDIUM TEMPERATURE MASKING TAPE



Product Features

Semi-Bleached Crepe Paper Masking Coated with Natural Rubber Adhesive

Application

Designed for transportation, marine and metal fabrication industries, as well as for wet sanding. It resists paint bleed-through, it can be used in temperatures up to 80°C and removes cleanly when the job is done

 Light Yellowish

Technical Data

Product	Max. Temp Resistance for 30min	Total Thickness (um)	Initial Tack (#)	Peel Adhesion (N/in)	Tensile Strength (N/in)	Elongation % at break
MTGP13-MT	80° C	130-140	8†	5†	50†	8%
MTGP15-MT	80° C	150-160	8†	6†	60†	8%

Product Characteristics

- Temperature-resistant up to 80° C
- Crepe paper backing provides easy tearing
- Excellent adhesion to metal, rubber, plastic and fiberglass
- Clean, flat edges for sharper paint lines
- Provides conformability on irregular surfaces and around corners
- Ideal for marking, temporary holding, wrapping and sealing
- Residue-free removal
- Solvent- and moisture-resistant

Product Sizes

Jumbo Roll Size :1250mm x 1500m
 Paper Core Size :76mm
 Cut Size :As per customer requirements

Shelf Life

12 Months Storage at 23° C and 65% Relative Humidity



Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.