

# **Product Features**

Woven Polyester & Cotton Blended with LDPE & Coated with Natural Rubber

# **Application**

For non-critical, general use in packaging, bundling, sealing, repairing, holding, book binding, carpet joining, taping / splicing insulation, reinforcing, patching, tabbing, marking & labelling

#### **Product Sizes**

Jumbo Roll Size :1060mm x 500m

Paper Core Size: 76mm

\* Contact sales representative for available sizes

#### **Shelf Life**

12 Months Storage at 23°C and 65% Relative Humidity



# Colours Silver Black Beige Dark Brown Red Yellow

Violet

Dark

Blue Light Light Blue Olive Green Sky Blue Green

Pink

Dark
Red



# Technical Data

	Product	Adhesive	Total Thickness		Initial Tack			Tensile Strength		Elongation % at break
			(um)	(mil)	(#)	(N/in)	ASTM D-3330 (oz/in)	(N/in)	ASTM D-3759 (lb/in)	ASTM D-3759
	CTNB23	Natural Rubber	230	9.1	15 <b>†</b>	8†	29	70 <b>t</b>	16	15%
	CTNB25	Natural Rubber	250	9.8	18†	8†	29	95 <b>†</b>	21	15%
	CTNB27	Natural Rubber	270	10.6	20t	81	29	95 <b>†</b>	21	15%
	CTNB30	Natural Rubber	300	11.8	23t	9†	32	95 <b>t</b>	21	15%
	CTNB36	Natural Rubber	360	14.2	25 <b>†</b>	9t	32	95†	21	15%
	CTNB42	Natural Rubber	420	17.5	25 <b>†</b>	10†	36	95 <b>t</b>	18	15%

# **Product Characteristics**

- Good conformability
- Designed for heavy duty
- Removes cleanly for up to three months when applied indoors
- Sticks immediately and stays on for up to one year without deterioration
- Strong water-resistant backing resists wear and light abrasion
- Provides a tight, moisture-resistant seal in many containment situations

isclaimer: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.



GTG MANUFACTURING SDN. BHD. (968289-M)

Website: www.gtggroup.com.my

Tel: +603-8725 9988 | Fax: +603-8725 9989 | Email: info@gtggroup.com.my











