

PRINTED CLOTH/ DUCT TAPE



Product Features

Woven Polyester & Cotton Blended with LDPE & Coated with Synthetic Rubber Adhesive

Application

Ideal for crafting, decorating and colour coding, patching, bundling, reinforcing, taping / splicing insulation, capping pipe, book binding, packaging, sealing, repairing, carpet joining, marking & labelling



Colours

* Colourful/ Printed/ Neon available

Technical Data

Product	Adhesive	Total Thickness		Initial Tack	Peel Adhesion		Tensile Strength		Elongation % at break
		(um)	(mil)	(#)	(N/in)	ASTM D-3330 (oz/in)	(N/in)	ASTM D-3759 (lb/in)	ASTM D-3759
CTP30-2	Synthetic Rubber	210	8.3	8 †	18 †	65	65 †	14	15%

Product Characteristics

- Durable, waterproof backing seals and protects against humidity
- Tears cleanly across and down for easy handling and application
- Aggressive, synthetic rubber adhesive provides instant adhesion to a wide variety of surfaces, including metal, glass, plastic and sealed concrete
- Tears easily by hand and provides ease of application and handling
- Conformable backing allows for performance in a variety of surface applications
- Tightly woven scrim provides high tensile strength, which is ideal for bundling applications

Product Sizes

Jumbo Roll Size : 1060mm x 500m
Paper Core Size : 76mm

* Contact sales representative for available sizes

Shelf Life

12 Months Storage at 23 °C and 65% Relative Humidity

Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.



GTG MANUFACTURING SDN. BHD. (968289-M)

Website: www.gtgroup.com.my

Tel: +603-8725 9988 | Fax: +603-8725 9989 | Email: info@gtgroup.com.my

