

Product Features

Premium Grade PVC Film Coated with Natural Rubber Adhesive for Marking Purposes

Application

Widely used in facility floor, lane, hazard warning, aisle marking, colour coding canister and storage container sealing, bundling, reinforcing, decorating and industrial applications

Product Sizes

Log Roll Size :1250mm x 30m

Paper Core Size: 76mm

* Contact sales representative for available sizes

Shelf Life

12 Months Storage at 23°C and 65% Relative Humidity



Technical Data

Product		Total Thickness		Peel Adhesion	Tensile Strength	Elongation % at break	Unwinding strength
	Troduct	(um)	(mil)	(N/in)	ASTM D-3759 (N/cm)	ASTM D-3759	(N/cm)
F	MT13	130	5.1	3.75	40	130%	2-4
F	MT15	150	5.9	3.75	40	140%	2-4
F	MT18	180	7.1	3.75	45	150%	2-4

Product Characteristics

- Highly Conformable
- Resistant to aging, UV, water, fungus, bacteria, oil, acid, alkali, solvent and corrosive chemicals
- Anti-abrasion and excellent tensile strength
- Excellent adhesion and good cohesion strength
- Excellent flexibility and good adhesion on uneven shapes and irregular surfaces, highly durable, unrolls quickly and easily tacks into any dry surface
- Can be easily removed without damaging the floor or leaving adhesive residue
- High visibility

claimer: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.



GTG MANUFACTURING SDN. BHD. (968289-M)

Website: www.gtggroup.com.my

Tel: +603-8725 9988 | Fax: +603-8725 9989 | Email: info@gtggroup.com.my











