

#### **Product Features**

Colour Biaxially Oriented
Polypropylene Film Coated with Water
Based Acrylic Adhesive

## **Application**

Widely used in industry for carton sealing, bundling, package beautifying and package identifying.

# **Product Sizes**

Paper Core Size: 76mm

\* Contact sales representative for available sizes

#### **Shelf Life**

12 Months Storage at 23°C and 65% Relative Humidity



# Colours Red Yellow Blue Green Purple Black White Orange

#### **Technical Data**

Product	Total Thickness	Peel Adhesion		Tensile Strength		Elongation % at break
	(um)	(N/in)	ASTM D-3330 (oz/in)	(N/in)	ASTM D-3759 (lb/in)	ASTM D-3759
OTC38	38	4t	14	60-100	17	100%
OTC40	40	41	14	60-100	17	100%
OTC42	42	4t	14	60-100	17	100%
OTC45	45	4.5t	16	70-110	19	100%
ОТС50	50	5t	18	70-110	19	100%
OTC65	65	6t	22	80-120	22	100%
ОТС70	70	6t	22	80-120	22	100%

### **Product Characteristics**

- Good holding power and economical for carton sealing
- Flexible and waterproof with superior stretch & puncture resistance
- Resistance to aging, weathering, UV light
- Highly conformable on most surfaces
- High shear strength, superior quick stick, easily applied
- Outstanding performance for majority of indoor usage
- Excellent viscosity and good bonding performance with high durability
- Maintain excellent tensile strength in a extreme change of surrounding temperature

er: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.



GTG MANUFACTURING SDN. BHD. (968289-M)

Website: www.gtggroup.com.my
Tel: +603-8725 9988 | Fax: +603-8725 9989 | Email: info@gtggroup.com.my











