

ALUGLASS TAPE



Product Features

Single Sided Aluminium Foil & Coated with Acrylic Solvent Adhesive

Application

Sealing, insulating, repairing & masking, main raw material for refrigerator factory, mobile phones, computers magnetic shielding place & construction industry

Colours



Silver

Silver (Foil) With White Release Liner

Technical Data

Product	Adhesive	Carrier Thickness	Peel Adhesion		Tensile Strength	
		(um)	(N/in)	ASTM D-3330 (oz/in)	(N/in)	ASTM D-3759 (lb/in)
AT614	Acrylic Solvent	60	14†	50	200†	45

Product Characteristics

- Superior stability during extreme fluctuations in temperature
- Resists water vapour, odour and smoke transmission
- Flame, weathering and UV retardant and high shear adhesion
- Resistant to chemicals to protect surfaces during de-paint process and other chemical masking operations
- Highly engineered acrylic adhesive provides long term durability, but removes cleanly after harsh masking applications
- Heat and light reflective tape protects surfaces and enhances lighting efficiency

Product Sizes

Jumbo Roll Size :1060mm x 1000m

Paper Core Size :76mm

* Contact sales representative for available sizes

Shelf Life

12 Months Storage at 23 °C and 65% Relative Humidity

Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.



GTG MANUFACTURING SDN. BHD. (968289-M)

Website: www.gtgroup.com.my

Tel: +603-8725 9988 | Fax: +603-8725 9989 | Email: info@gtgroup.com.my

