

# FILAMENT TAPE

## - CROSSED LINE



### Product Features

BOPP Film with Reinforced Glass Yarn  
Filament Coated with Synthetic  
Rubber Adhesive

### Application

Great for heavy-duty splicing, packing, bundling, reinforcing and palletizing. Ideal for heavy-weight packages overseas/ export packing and shipping



### Colours



White

### Technical Data

Product	Woven	Total Thickness		Initial Tack (#)	Peel Adhesion		Tensile Strength		Elongation % at break ASTM D-3759
		(um)	(mil)		(N/in)	ASTM D-3330 (oz/in)	(N/in)	ASTM D-3759 (lb/in)	
FTCW12	Cross Weave	120	4.7	8	6	22	600	134	12%
FTCW14	Cross Weave	140	5.5	10	18	65	800	180	12%
FTCW17	Cross Weave	170	6.7	12	20	72	1000	220	12%

### Product Characteristics

- Glass yarn filaments add strength for box closing and bundling
- Excellent long term holding power
- High shear, high tack adhesive for strong holding power
- Hold instantly with minimum rubdown
- Nicks, abrasion, scuffing resistant
- Moisture resistance, superior resistance against mildew and mold
- Weatherproof, UV and temperature resistant
- Bi-directionally fibreglass reinforced tape provides cut and tear resistance in machine direction and cross direction
- Able to withstand roughest shipping and handling conditions

### Product Sizes

Jumbo Roll Size :1060mm x 1000m

Paper Core Size :76mm

\* Contact sales representative for available sizes

### Shelf Life

12 Months Storage at 23°C and 65% Relative Humidity

*Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.*



**GTG MANUFACTURING SDN. BHD. (968289-M)**

Website: [www.gtgroup.com.my](http://www.gtgroup.com.my)

Tel: +603-8725 9988 | Fax: +603-8725 9989 | Email: [info@gtgroup.com.my](mailto:info@gtgroup.com.my)

