

Product Features

LLDPE Stretch Wrap Film

Application

Unitise pallet loads boxes or bundling small items for efficient handling & storage to ensure safe & secure delivery of packages



Colours

Black









Technical Data

Thickness (um)	20-22
Tensile Strength Lengthway (%)	≥350
Tensile Strength Crossway (%)	≥600
Adhesion After 100% Extension	≥2

^{*}The above spec is subjected to min tolerance of \pm 10%

Product Characteristics

- Strong, high puncture & tear resistance
- Superior clarity & low noise during unwind
- Provides protection from dust, dirt, moisture or oil
- Excellent load retaining capability
- Requires no additional adhesives. It is self-adhesive
- Leaves no residue
- Coloured/printed stretch film are available upon request
- Products are ROHS compliant

Product Sizes

Roll Size :500mm x 2.4 Kg

* Contact sales representative for available sizes

Shelf Life

12 Months Storage at 23 °C and 65% Relative Humidity

Disclaimer :

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.





Website: www.gtggroup.com.my

Tel: +603-8725 9988 | Fax: +603-8725 9989 | Email: info@gtggroup.com.my











