

PROTECTIVE FILM FOR CARPET



Product Features

Special Formulated Polyethylene Film as Substrate and Acrylic as Pressure Sensitive Adhesive



Acrylic Pressure Sensitive Adhesive Film
PE Base Film

Application

Provide surface protection for carpet and decorative surface in fibre texture



Colours



Transparent



Blue



Green



Cream



Black & White



Yellow & White

Technical Data

Base Film Thickness (μm)	50-200
Adhesive Thickness (μm)	5-30
Peel Strength 180 °C (g/cm)	80-400
Horizontal Elongation at Break (%)	400-700
Vertical Elongation at Break (%)	200-300
Heat Resistance (°C)	60

Product Characteristics

- Highly conformable on most surfaces
- Easy to peel off without residue left
- Anti-corrosion
- Weather resistance

Product Sizes

Roll Sizes : (500-2100)mm x (500-1500)m

Shelf Life

12 Months Storage at 23 °C and 65% Relative Humidity

Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.



GTG MANUFACTURING SDN. BHD. (968289-M)

Website: www.gtgroup.com.my

Tel: +603-8725 9988 | Fax: +603-8725 9989 | Email: info@gtgroup.com.my

