

PROTECTIVE FILM FOR GLASS PANEL



Product Features

Special Formulated Polyethylene Film as Substrate and Solvent / Water as Pressure Sensitive Adhesive



Acrylic Pressure Sensitive Adhesive Film
PE Base Film

Application

Provide surface protection for glass, mirrors and other glass products



Colours



Transparent



Blue



Green



Cream



Black & White



Yellow & White

Technical Data

Base Film Thickness (μm)	30-200
Adhesive Thickness (μm)	5-30
Peel Strength 180 °C (g/cm)	60-400
Horizontal Elongation at Break (%)	150-300
Vertical Elongation at Break (%)	150-200
Heat Resistance (°C)	60

Product Characteristics

- Flexible and soft
- Highly conformable on most surfaces
- Easy to peel off without residue left
- Excellent insulation
- Moisture-proof
- Anti-corrosion

Product Sizes

Roll Size : (500-2100)mm x (500-1500)m

Shelf Life

12 Months Storage at 23 °C and 65% Relative Humidity

Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.



GTG MANUFACTURING SDN. BHD. (968289-M)

Website: www.gtgroup.com.my

Tel: +603-8725 9988 | Fax: +603-8725 9989 | Email: info@gtgroup.com.my

