

# PROTECTIVE FILM FOR CERAMIC



## Product Features

Special Formulated Polyethylene Film as Substrate and Solvent/Water as Pressure Sensitive Adhesive



## Application

Provide surface protection for ceramic tile and other ceramic products



## Colours



## Technical Data

Base Film Thickness (µm)	30-200
Adhesive Thickness (µm)	2-20
Peel Strength 180° C (g/cm)	30-180
Horizontal Elongation at Break (%)	300-600
Vertical Elongation at Break (%)	200-300
Heat Resistance (°C)	60

## Product Characteristics

- Good stability of the pressure sensitive adhesive
- Flexible & soft
- Anti-corrosion
- No residue left after removal

## Product Sizes

Roll Size : (500-2100)mm x (500-1500)m

## Shelf Life

12 Months Storage at 23° C and 65% Relative Humidity

*Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.*



**GTG MANUFACTURING SDN. BHD. (968289-M)**

Website: [www.gtgroup.com.my](http://www.gtgroup.com.my)

Tel: +603-8725 9988 | Fax: +603-8725 9989 | Email: [info@gtgroup.com.my](mailto:info@gtgroup.com.my)

