

OPP TAPE



Product Features

Biaxially Oriented Polypropylene Film
Coated with Water Based Acrylic
Adhesive

Application

Commonly used for heavy-duty carton sealing, industrial packaging as well as product bundling and wrapping purposes

Product Sizes

Paper Core Size :76mm

* Contact sales representative for available sizes

Shelf Life

12 Months Storage at 23°C and 65% Relative Humidity

Colours



Technical Data

Product	Total Thickness (um)	Peel Adhesion		Tensile Strength		Elongation % at break ASTM D-3759
		(N/in)	ASTM D-3330 (oz/in)	(N/in)	ASTM D-3759 (lb/in)	
OTT38	38	4↑	14	60-100	17	100%
OTT40	40	4↑	14	60-100	17	100%
OTT42	42	4↑	14	60-100	17	100%
OTT45	45	4.5↑	16	70-110	19	100%
OTT50	50	5↑	18	70-110	19	100%
OTT65	65	6↑	22	80-120	22	100%
OTT70	70	6↑	22	80-120	22	100%
OTB40	40	4↑	14	60-100	17	100%
OTB45	45	4.5↑	16	60-100	17	100%
OTB50	50	5↑	18	70-110	17	100%

Product Characteristics

- Good holding power and economical for carton sealing
- Excellent resistant to ultra-violet light (UV), aging, cold, heat, water and other weather conditions
- Highly conformable on most surfaces
- Excellent clarity, high shear strength, superior quick stick
- Excellent viscosity and good bonding performance with high durability
- Good cutting effect and excellent operation with general purpose packaging machines

Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.



GTG MANUFACTURING SDN. BHD. (968289-M)

Website: www.gtgroup.com.my

Tel: +603-8725 9988 | Fax: +603-8725 9989 | Email: info@gtgroup.com.my

