

PRINTED OPP TAPE



Product Features

Printed Bi-Oriented Polypropylene Tape
Coated with Acrylic Water Based
Adhesive

Application

Commonly used for carton sealing with logo printed, industrial packaging and product bundling such as vegetables & fruits, medical product, furniture, scientific apparatus, electronic products

Product Sizes

Paper Core Size :76mm

* Contact sales representative for available sizes

Shelf Life

12 Months Storage at 23°C and 65%
Relative Humidity



Colours

- *Customize printing (Maximum 3 Colours Printing)
- *Different Logos, Texts & Colours Can Be Printed (Reversed Printing)

Technical Data

| Product | Total Thickness | Peel Adhesion | | Tensile Strength | | Elongation % at break |
|---------|-----------------|---------------|---------------------|------------------|---------------------|-----------------------|
| | (um) | (N/in) | ASTM D-3330 (oz/in) | (N/in) | ASTM D-3759 (lb/in) | ASTM D-3759 |
| OTP50 | 50 | 5↑ | 17 | 60-100 | 17 | 100% |
| OTP55 | 55 | 5↑ | 17 | 70-100 | 19 | 100% |

Product Characteristics

- Custom printed carrier is able to meet requirements and convenient to product information labelling
- Excellent adhesion and easy to apply because of good flexibility possess smooth and glossy surface with excellent water resistance properties
- Strong initial binding force enable permanent bonding effect with one-touch sticky when applied on substrates
- Good insulation and strong strength of adhesive make it suitable for outdoor usage
- Outstanding performance to resist coldness and maintain good adhesion in moisture condition
- Well adaptation over extreme change of weather temperature
- Highly conformable on most surfaces
- High shear strength, superior quick stick
- Increase security during product transition in shipping departments or long distance transportation
- Good thermal insulation

Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.



GTG MANUFACTURING SDN. BHD. (968289-M)

Website: www.gtgroup.com.my

Tel: +603-8725 9988 | Fax: +603-8725 9989 | Email: info@gtgroup.com.my

